

CONGRATULATIONS ON THE PURCHASE OF YOUR DES SOL PRODUCT.

Part Number : DSJL-G4
Part Description : Des Sol Ladder GEN4
Vehicle : Suzuki Jimny 2018 – Current

WARNING

NOTE THE FOLLOWING:

- THIS PRODUCT MUST BE INSTALLED EXACTLY AS PER THE FITTING INSTRUCTIONS BELOW AND ONLY THE HARDWARE SUPPLIED WITH THIS PACK IS TO BE USED
- IN THE EVENT OF DAMAGE TO THE LADDER, CONTACT YOUR NEAREST DES SOL SUPPLIER – REPAIRS OR MODIFICATIONS MUST NOT BE ATTEMPTED ON THE LADDER
- THIS PRODUCT AND MOUNTING COMPONENTS MUST NOT BE MODIFIED IN ANY WAY
- DO NOT REMOVE LABELS FROM THIS PRODUCT

Tools required for installation:

- Ratchet & Sockets:
 - 5mm hex bit
- Allen keys
 - 5mm Hex key

ITEMS CONTAINED IN THIS KIT

Ladder Frame	1 x Aluminium Ladder frame
Brackets	1 x top left Bracket 1x top Right bracket 2 x bottom brackets
Fasteners	4 x M8 X 30 Stainless steel button head cap screws 4 x M8 Stainless steel spring washers 4 x M8 Stainless steel flat washers

GEN 4 LADDER FITMENT

	<ol style="list-style-type: none">1. Remove Bottom brackets from ladder and position as per image with the bolts loose, the bolts must just be taking in the threads of the nut
	<ol style="list-style-type: none">2. Ensure top bracket bolts are loose and positioned correctly. The bracket with a notch must go on the Right – See bracket circled in red.
	<ol style="list-style-type: none">3. With the door open hook the top brackets onto top right hand side of the door4. Leave a 15mm gap from the right side of the door to the bracket (This position will accommodate for a bigger tyre mounted on the back door)



5. Pull down on the bottom rung of the ladder until the bottom brackets clear the bottom edge of the door and push forward



6. Tighten the bottom brackets first and torque the bolts to 10Nm



7. Tighten the top bolts and torque to 7 Nm